

Kompozitní hadice pro chemikálie ALFAKEN 5J551EN, 10bar, EN13765, elektrostaticky vodivá

↔		↔		⌚		⤴))		🏠	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
40	1 1/2	52	2,05	10	150	140	5,50	90	1,400	0,940	
50	2	62	2,44	10	150	150	6,00	90	1,600	1,074	
65	2 5/8	77	3,03	10	150	175	7,00	90	2,100	1,410	
80	3 1/8	93	3,66	10	150	250	10,00	90	2,800	1,880	
100	4	121	4,76	10	150	350	14,00	90	4,800	3,223	
NA		LA		NEU		EMEA		SA		AP AU	



5J551 EN

**Acid-chemical S&D 10 bar (150 psi)
standard duty**

EN 13765 arrêté TMD

Inner wire: Polypropylene coated steel wire

Tube: Polypropylene film

Cover: Grey PVC coated fabric with longitudinal white stripe

Outer wire: Galvanised steel wire

Use: Acid and chemical suction and delivery. Specially designed for tank truck applications

Safety factor: 4:1

Temperature: -30 °C +80 °C (-22 °F +176 °F)

Electrical Conductivity: Ensured by the 2 wires in contact with fittings

Electrical Resistance: ≤ 2.5 Ohm/mt up to DN 50mm (2");
≤ 1 Ohm/mt over DN 50mm (2")