



Industrie Plastiche Lombarde S.p.A.

# MERCURIO M



**Colour:** inside black and outside blue

**Temperature range:** -10°C + 60°C

**Features:** PVC layflat hose, reinforced with Polyester braided yarn

Light and easy handling, resistant to ageing, UV rays, hydrolysis, atmospheric agents, microbes and most chemicals.

**Applications** excellent for irrigation and delivery of fertilizers, acids and chemical solutions.

IPL's technical data sheets contain products general features, the data do not constitute product specification. The information given by IPL team are based on the best knowledge, but do not exempt the client to carry out controls on IPL's products in order to estimate the real technical suitability for the intended application. The applications are out of IPL control possibility and fall under the responsibility of the end user





Industrie Plastiche Lombarde S.p.A.

# MERCURIO M



→ Textile reinforcement

Technical data

Code	out. Ø	Ins. Ø	weight	WP	BP	Coil lgth.
		mm	g/m	bar	bar	m
MM 01 020.0 000.0		20	160	10	30	50
MM 01 025.0 000.0	1"	25	190	10	30	50
MM 01 030.0 000.0		30	230	10	30	50
MM 01 032.0 000.0	1 ¼"	32	240	9	27	50
MM 01 035.0 000.0		35	280	8	24	50
MM 01 038.0 000.0	1 ½"	38,1	300	8	24	50
MM 01 040.0 000.0		40	320	8	24	50
MM 01 045.0 000.0		45	350	8	24	50
MM 01 052.0 000.0	2"	52	410	8	24	50
MM 01 060.0 000.0		60	540	8	24	50
MM 01 063.0 000.0	2 ½"	63,5	560	8	24	50
MM 01 070.0 000.0		70	620	7	21	50
MM 01 076.0 000.0	3"	76,2	680	7	21	50
MM 01 080.0 000.0		81	740	7	21	50
MM 01 090.0 000.0		90	870	7	21	50
MM 01 102.0 000.0	4"	102	1000	7	21	50
MM 01 110.0 000.0		110	1150	7	21	50
MM 01 127.0 000.0	5"	127	1350	6	18	50
MM 01 153.0 000.0	6"	153	1650	4	12	50
MM 01 203.0 000.0	8"	203	2300	2,5	7,5	50

The technical data here reported were measured at 23 °C with 50% humidity